



- NOTES:
- MILD STEEL OR STAINLESS CONSTRUCTION.
 - FLOWMETER SUPPORT SHOULD BE RIGID AND INDEPENDENT OF HOUSING (CABINET)
 - ANY MODIFICATION OR CHANGE SHOULD BE APPROVED BY SIEMENS MILLTRONICS.
 - SEE DATA SHEET FOR MATERIAL SPECIFICATIONS.
 - SEE INSTRUCTION MANUAL FOR LEVELING THE FLOWMETER SENSING HEAD.
 - () INDICATES DIMENSIONS IN MILLIMETERS.

2		ADD MILLTRONICS TO PRODUCT NAME/UPDATE BORDER PER ECN 2003-0288	RPC	PTR	DEC 19/03
USE DIMENSIONS ONLY - DO NOT SCALE		REPLACES 1-7530007Z-DP-B REV 1	1		
DIMENSIONS ARE IN INCHES		Rev.	Revision / ECN Description	Drawn	Appr.
Third Angle Projection		Product Group	Tolerance Unless Otherwise Noted:	UOS	Scale:
		MASS DYNAMICS	1 Place Decimal ± 0.03	Angles:	Size:
		Date: 25 OCT 90	2 Place Decimal ± 0.01	± 0.5°	B
FOR INTERNAL USE ONLY		Drawn: D. McCONNELL	TITLE:		
		Checked:	MILLTRONICS E-300 FLOWMETER, c/w 16" (406) INLET OUTLINE DIMENSIONS		
		Approved:	DRAWING No: 23650473		
		Location: PETERBOROUGH	Rev. 2		
SIEMENS MILLTRONICS PROCESS INSTRUMENTS INC. Peterborough, Ontario, Canada		DRAWING No: 23650473		Rev. 2	
File No. 2365047302		Plot at: 1= 16		Sheet 1 of 1	