



TO
BW500/SF500 **BW100**

TB1

TB1

- 11
- 12
- 14
- 13
- 1
- 2
- 3
- 4

- 20
- 19
- 17
- 18
- 4
- 3
- 2
- 1

HAZARDOUS AREA **SAFE AREA**

USE	BARRIER ID. #
+ EXCITATION	9001/01-083-442-10
+ SENSE	9001/02-133-150-10
- EXCITATION	9001/00-083-442-10
- SENSE	9001/02-133-150-10
SIGNAL A ±	9002/22-093-040-00
SIGNAL B ±	9002/22-093-040-00

- NOTES**
- ALL DIMENSIONS ARE INCHES () DENOTES mm.
 - USED WITH ACCUMASS BW500.
 - FOR CABLE RUNS OVER 500 FT. JUMPERS J1 & J2 MUST BE REMOVED AND ADDITIONAL CONDUCTORS SUPPLIED.

2	REMOVE CONFIDENTIAL NOTICE PER ECN 2004-0001	RPC	PTR	FEB 23/2004
1	CHANGE TITLE & ADD SF500, BW100 PER ECN 2002-0147	RPC	PTR	JUNE 18/02

USE DIMENSIONS ONLY - DO NOT SCALE		REPLACES 0-7330002Z-DI-B REV 0	
DIMENSIONS ARE IN INCHES		Rev.	Revision / ECN Description
<p>For Public Release</p>	Product Group	MASS DYNAMICS	Tolerance Unless Otherwise Noted: UOS
	Date:	19 FEB 99	1 Place Decimal ± 0.03 Angles: ± 0.5°
	Drawn:	R. CLYSDALE	2 Place Decimal ± 0.01
	Checked:	P. RICCI	3 Place Decimal ± 0.002
	Approved:	R. CLOSS	Scale: NTS
Location:	PETERBOROUGH	TITLE: STAHL BARRIER PKG., TWO LOAD CELLS & INTEGRATOR INTERCONNECTION DRAWING	
SIEMENS MILLTRONICS PROCESS INSTRUMENTS INC. Peterborough, Ontario, Canada	DRAWING No:	23650343	Rev. 2
File No. 2365034302	Plot at: 1=1	Sheet 1	Of 1