



SEE INSTRUCTION MANUAL FOR PROPER OPERATION.

NOTES:

- 1) FOR FURTHER INFORMATION, REFER TO THE BELT SCALE INSTALLATION DIAGRAM, THE MD-256 SPEED SENSOR INSTRUCTION MANUAL, OR CONTACT THE NEAREST SIEMENS MILLTRONICS REPRESENTATIVE.
- 2) THE MD-256 IS A UNIDIRECTIONAL DEVICE. CLOCKWISE ROTATION PRODUCES PULSES AT TERMINAL #2, AND COUNTER-CLOCKWISE ROTATION PRODUCES PULSES AT TERMINAL #3. WIRING SHOWN IS FOR CLOCKWISE ROTATION.

USE DIMENSIONS ONLY - DO NOT SCALE		2	DRAWING REPLACES 0-74300042-DU-B UPDATED WITH SIEMENS TITLE BLOCK	JLC	RDC	JULY 24/03
DIMENSIONS ARE IN INCHES		Rev.	Revision / ECN Description	Drawn	Appr.	Date
Third Angle Projection 	Product Group	MASS DYNAMICS		Tolerance Unless Otherwise Noted:	U05	Scale:
	Date:	10/03/98		1 Place Decimal ±0.05	Angles: ±0.5°	NONE
FOR INTERNAL USE ONLY	Drawn:	B. GRAY		2 Place Decimal ±0.01		Size:
	Checked:	P. RICCI		3 Place Decimal ±0.002		B
	Approved:	R. CLOSS		TITLE:		
	Location:	PETERBOROUGH		MILLTRONICS MD-256 CUSTOMER WIRING AND OUTLINE DIAGRAM		
	SIEMENS MILLTRONICS PROCESS INSTRUMENTS INC. Peterborough, Ontario, Canada	DRAWING No:		23650444		Rev.
	File No. 2365044402	Pkt at: 1:1		Sheet 1 of 1		2